



The Gorman-Rupp Company

GMS Series (G Series)

The GMS Series is designed for intermittent or medium duty service for applications in the operating ranges noted. These units are available with head and backhead jackets for temperature control, carbon graphite bushings for low viscosity liquids, silicon carbide bushings for wear resistance. For continuous duty service, or for handling viscous liquids, see heavy duty GHC pumps.



Specifications

Size:	1" (25 mm), 1-1/2" (37.5 mm), 2" (50 mm), 2-1/2" (62.5 mm), 3" (75 mm), 4" (100 mm), 5" (125 mm), 6" (150 mm)
Max Capacity:	480 GPM (30 lps)
Max Viscosity:	250,000 SSU (54,000 cST)
Max Pressure:	125 PSI (9 BAR)
Min Temperature:	-40 F (-40 C)
Max Temperature:	300 F (149 C)
Materials of Construction:	Cast Iron

Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.



The Gorman-Rupp Company
P.O. Box 1217
Mansfield, Ohio 44901-1217
Tel: 419-755-1011
Fax: 419-755-1251
E-mail:
grsales@gormanrupp.com

The Gorman-Rupp International Company
P.O. Box 1217
Mansfield, Ohio 44901-1217
Tel: 419-755-1011
Fax: 419-755-1266
E-mail: intsales@gormanrupp.com

Gorman-Rupp of Canada, Ltd.
70 Burwell Road
St. Thomas, Ontario N5P 3R7,
Canada
Tel: 519-631-2870
Fax: 519-631-4624
E-mail: grcanada@grcanada.com



www.gormanrupp.com

©2005, The Gorman-Rupp Company, All Rights Reserved